



37TH INTERNATIONAL
NO-DIG
FLORENCE 2019

Fortezza da Basso • FLORENCE (Italy)

30th September • 2nd October 2019

SELECTION OF CRITERIA AND METHODS FOR A COMPARATIVE EVALUATION OF ENVIRONMENTAL SUSTAINABILITY OF OPEN-CUT AND NO-DIG TECHNOLOGIES FOR NEW INSTALLATIONS AND IN SITU REHABILITATION OF SEWER PIPES

Martina Ferrini¹, Valentina Castellani², Nadia Mirabella³, Serenella Sala⁴, Stefano Tani⁵ and Valeria Mezzanotte¹

¹ DISAT, Università degli Studi di Milano Bicocca, Piazza della Scienza, 1, 20126 Milano, Italy


² Sustainability Consultant


³ KU Leuven, Department of Architecture, Kasteelpark Arenberg 1, 3001, Leuven, Belgium

⁴ JRC Ispra (VA), Italy

⁵ MM SpA

Technological assessment is necessary when the development of new technologies can potentially cause a series of undesirable effects from a social, occupational, environmental, cultural, technical and economic standpoint





NO-DIG TECHNOLOGY


Rehabilitation of
existing sewers
by CIPP
technologies

TRADITIONAL OPEN-CUT

Construction of
a new sewerage
system

Sustainability Assessment of Technologies (SAT)

Term used to describe
a complex approach
to appraise the sustainability
of different technologies



Approach adopted for sustainability assessment




37TH INTERNATIONAL
No - DIG
FLORENCE 2019


- ☐ Efficiency of both material and energy resources
- ☐ Process and logistics optimization
- ☐ Reduction of overall environmental impact
- ☐ Financial profitability
- ☐ Ability to generate positive economic and social effects in the local context
- ☐ Environmental, economic and social sustainability

Criteria

Set of indicators


**Sustainability
assessment
of the considered
system**





Environmental impacts

Development of a **LCA** analysis to quantify the potential environmental impacts




Economic costs

Direct costs directly linked to the construction of the project; they refer to the costs of conception, development and implementation

Social impacts and costs

Generalised indirect costs (**IGC**) and costs related to potential community risks

Assessment of environmental impacts




System boundaries No-dig construction site

1. Preliminary inspection
and cleaning

2. Preparation of the site
and of the liner

3. Liner insertion
and polymerization

4. Rehabilitation of
the inspection
chambers



System boundaries Open-cut construction site



37TH INTERNATIONAL
NO-DIG
FLORENCE 2019


1. Traffic diversion and road safety measures

3. Excavation and new pipe laying

2. Scarification and removal of the road surface


4. Filling the trench with sand, excavated earth and temporary asphalt

5. Final phase of asphalt optimization




Case A: no-dig

Relative percent contribution
of the main
construction phases
to overall
environmental impact
for each
impact category




Case B: open-cut

Relative percent contribution
of the main
construction phases
to overall
environmental impact
for each
impact category



Direct costs



Case A: no-dig

Length of the rehabilitation section
465.23 meters

Total amount estimated by CME:
€ 393,894

Estimated amount on 100 linear
meters: € 84.708,41



Case B: open-cut

Length of the section about 820
meters

Total amount estimated by CME:
€ 932,087

Estimated amount on 100 linear
meters: €113.669,25

Social costs



Indirect Generalized Cost (IGC)

- Vehicle operating costs
 - Traffic delay
- Loss of parking areas
- Air, water, acoustic pollution

Social costs related to the risk

- Accidents to workers, or users
 - Damage to infrastructures, or properties

Example: Calculation of Traffic Delay Cost (TDC)

$$DT = Lw / Sw - Ln / Sn$$

$$CD = DT \times VOT \times ANP$$

$$TDC = CD \times NVD \times D$$

Lw: Length of the work area including deviations (km)

Sw: speed through the work area (km / h)

Ln: Length of the work area in normal conditions (km)

Sn: normal speed (km / h)

DT = Delay Time (h)

VOT = value of time (euro / person * hour)

ANP = average number of people per vehicle.

NVD = n. of vehicles per day

D = duration of the construction works



For the no-dig construction site, the traffic delay is less than the traffic delay in the case of an open-cut construction site.

Conclusions



37TH INTERNATIONAL
NO - DIG
FLORENCE 2019






Thanks for your attention!

Comparison between case A and case B

Comparison
of the overall impacts
between case A (no-dig)
and case B (open-cut)





37TH INTERNATIONAL
NO - DIG
FLORENCE 2019



37TH INTERNATIONAL
NO - DIG
FLORENCE 2019



37TH INTERNATIONAL
NO - DIG
FLORENCE 2019



37TH INTERNATIONAL
NO - DIG
FLORENCE 2019